

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

367.40544X00



Applicant(s): MCCARTHY, Kevin
Serial No.: Not yet assigned
Filed: August 31, 2001
Title: HANDSET PERSONALISATION
Group: Not yet assigned

LETTER CLAIMING RIGHT OF PRIORITY

Honorable Commissioner of
Patents and Trademarks
Washington, D.C. 20231

August 31, 2001


Sir:

Under the provisions of 35 USC 119 and 37 CFR 1.55, the applicant(s) hereby claim(s) the right of priority based on United Kingdom Patent Application No.(s) 0021451.0, filed August 31, 2000.

A certified copy of said United Kingdom Application is attached.

Respectfully submitted,

ANTONELLI, TERRY, STOUT & KRAUS, LLP



Donald E. Stout
Registration No. 26,422

DES/alb
Attachment
(703)312-6600

This Page Blank (uspto)



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ



CERTIFIED COPY OF PRIORITY DOCUMENT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.


In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated: 25 June 2001



This Page Blank (uspto)

01SEP00 E565111-1 002716
P01/7700 0.00-0021451.0

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

PAT 00319 GB

2. Patent application number

(The Patent Office will fill in this part)

31 AUG 2000

0021451.0

3. Full name, address and postcode of the or of each applicant (underline all surnames)

NOKIA MOBILE PHONES LIMITED
KEILALAHDENTIE 4
02150 ESPOO
FINLAND

Patents ADP number (if you know it)

05911995004

If the applicant is a corporate body, give the country/state of its incorporation

FINLAND

4. Title of the invention

HANDSET PERSONALISATION

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

NOKIA IPR DEPARTMENT
NOKIA HOUSE
SUMMIT AVENUE
FARNBOROUGH
HAMPSHIRE
GU140NG UK

Patents ADP number (if you know it)

7577638001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

YES

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

21

Claim(s)

4

Abstract

1

Drawing(s)

7+7

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

1

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

K L Jeffery

Date

KENDRA JEFFERY

29.8.2000

12. Name and daytime telephone number of person to contact in the United Kingdom

Mr A Franks 01252 865015

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

Handset Personalisation

5 The invention relates to the personalisation of a communication terminal, e.g. handportable phone.

During the past few years cellular terminals have changed appearance from heavy brick formed electronic boxes towards an attractive design.

10 Furthermore the users wants to personalize their phones by using colored, exchangeable covers, certain ringing tones, etc.

According to a first aspect of the invention there is provided method of handling operating characteristics of a profile in a communication terminal, said communication terminal has a number of user selectable profiles each
15 including a group of user adjustable operating characteristics, comprising reception of a message including a group of user adjustable operating characteristics from a remote terminal sent via a communication channel, and saving said group of user adjustable operating characteristics as a profile in said communication terminal. Hereby it becomes possible to define new
20 profiles in a terminal by transmitting a profile from another remote profile via the communication network (over the air).

Preferably the transmitted profile message includes a ringing tone and at least one graphical picture for being stored in a profile selected by the user.
25 According to the preferred embodiment the communication terminal allows the user to discard a received profile message after inspection of items included in the profile message. The data contained in the profile message includes according to the preferred embodiment a plurality of individual pictures, and said pictures are displayed successively in order to create an animation. The
30 profile message may furthermore include a name label for the profile.

According to a second aspect of the invention there is provided a communication terminal having a number of user selectable profiles each including a group of user adjustable operating characteristics, and comprising
5 means for receiving messages, means for analysing the message type and for detecting user adjustable operating characteristics when present in the message, and means for storing user adjustable operating characteristics as one of said number of user selectable profiles available in said communication terminal.

10 According to a third aspect of the invention there is provided a method of providing operating characteristics for a profile for a communication terminal, said communication terminal has a number of user selectable profiles each including a group of user adjustable operating characteristics, comprising
15 arranging a group of user adjustable operating characteristics in a message having a predetermined message format, and transmitting said message to said communication terminal via a communication channel.

According to a fourth aspect of the invention there is provided a
20 communication terminal having a number of user selectable profiles each including a group of user adjustable operating characteristics, and comprising means for arranging a group of user adjustable operating characteristics in a message having a predetermined message format, and means for transmitting said message to said communication terminal via a
25 communication channel.

For a better understanding of the present invention and to understand how the same may be brought into effect reference will now be made by way of example only to the accompanying drawings in which: -

Brief Description of the Drawing

Fig. 1 illustrates a preferred embodiment of a communication terminal according to the invention.

- 5 Fig. 2 schematically shows the essential parts of a communication terminal for communication with a cellular network.

Fig. 3 shows a sequence of display for profile selection in a preferred embodiment of a communication terminal according to the invention.

10

Fig. 4 shows a sequence of display for profile editing in a preferred embodiment of a communication terminal according to the invention.

- 15 Fig. 5 shows network in which profiles of terminals may be transferred according to the invention.

Fig. 6 is a flow diagram for illustrating the profile message reception in a preferred embodiment of a communication terminal according to the invention.

- 20 Fig. 7 shows a sequence of display for profile message reception in a preferred embodiment of a communication terminal according to the invention.

Detailed Description of Embodiments

- 25 Fig. 1 shows a preferred embodiment of a phone according to the invention, and it will be seen that the phone, which is generally designated by 1, comprises a user interface having a keypad 2, a display 3, an on/off button 4 (present in the top of the phone and therefore not visible in the present view), a speaker 5, and a microphone 6 (openings present in the bottom of the phone and therefore not visible in the present view). The phone 1 according

to the preferred embodiment is adapted for communication via a cellular network, such as the GSM 900/1800 MHz network.

According to the preferred embodiment the keypad 2 has a first group 7 of
5 keys as alphanumeric keys, one softkey 8, a cursor navigation key 10 (scroll
up/down), and a "clear"-key 9 for erasing letters in text in the display 3,
jumping steps down in the menu structure and rejecting calls. The present
functionality of the soft key 8 is shown in separate fields (softkey-label) in the
display 3 just above the softkey 8. The softkey 8 is a multifunction key and its
10 present function depends on the state of the phone 1. The softkey 8 gives
access to the menu, the phonebook and call handling.

Fig. 2 schematically shows the most important parts of a preferred
embodiment of the phone, said parts being essential to the understanding of
15 the invention. The processor 18 controls the communication with the network
via the transmitter/receiver circuit 19 and an internal antenna 20.

The microphone 6 transforms the user's speech into analogue signals, the
analogue signals formed thereby are A/D converted in an A/D converter (not
20 shown) before the speech is encoded in a digital signal processing unit 14
(DSP). The encoded speech signal is transferred to the processor 18, which
i.a. supports the GSM terminal software. The processor 18 also forms the
interface to the peripheral units of the apparatus, including a RAM memory
17a and a Flash ROM memory 17b, a SIM card 16, the display 3 and the
25 keypad 2 (as well as data, power supply, etc.). The digital signal-processing
unit 14 speech-decodes the signal, which is transferred from the processor 18
to the earpiece 5 via a D/A converter (not shown).

The mobile station main control circuit, including the processor 18 (can be
30 implemented as several micro-controllers) and blocks 30-33 for controlling

transmission of profiles as short messages according to the present invention. The blocks 30-33 can be interpreted as a data processing unit of the terminal, which can be formed in full by programming the processor 18.

- 5 In the following the operation of the terminal will be discussed with focus on the transmission of profiles including ringing tones, graphics and name of the profile. By means of the user interface (keyboard 2 and the display 3), the desired profile is retrieved from the memory. When the user enters a command to send a profile, the processor 18 forms a message including a
- 10 standard message header, and the content of the message data line has a sequence of characters forming an identifier at the beginning of the line followed by a sequence of bits representing the profile including the elements of the profile.
- 15 The processor 18 comprises character transformation functions, which have been implemented as software, and by means of which the processor 18 processes the characters. The processor 18 transfers the line of characters formed to an SMS transmission controller 31, which adds to the message header including message address information, i.e., the information on the
- 20 destination on the basis of the user input information. The transformation of the profile and its individual elements into characters is preferably implemented as an application program that is run by the processor 18.

- When the address information has been added at the SMS transmission
- 25 controller 31, the message is transferred into an outbox 32, which sends the message, and which has access to a buffer, in which the message is stored until a successful transmission has been reported. If the transmission fails, the outbox 32 re-transmits the message. When the transmitter/ receiver circuit 19 has network coverage and is idle, the message is transferred to an SMS
- 30 transmission driver circuit 33 by the controller 18 which adds the header to the

message information relating to the mobile communications system in question, such as validity information (which indicates in which direction the message is going, i.e., from a mobile station to a message service centre or vice versa), processes the address information into a form required by the mobile communications system, and adds to the message the address of the message service centre, as well as the short message identifier, and forms the information to be transmitted, e.g., a digital signal for a transmitter 19.

The operations provided by the processor 18, the SMS transmission control unit 31, the SMS outbox 32 and the SMS transmission driver 33 can also be provided as an application run on a Personal Computer 57 (see fig. 5), which may have a connection to a short message service centre via the Internet.

When a communication terminal 1 receives a profile included in a short message, the message is received through the transmitter / receiver unit 19 and is passed into a destination box or an inbox 30 of the data processing unit including a memory for storing the message. The received message can be stored in a memory located in the SIM card. First the type of message is detected, and if the received message is an ordinary short message, the processor 18 notifies in the display 3 that short message received.

If the message has an identifier indicating that the message includes a profile, the processor 18 will further search for an element identifying the individual elements of the profile. When the elements have been identified, the processor 18 starts to process the received data. For the name of the profile, the processor 18 performs a transformation of the binary characters into ASCII characters and identifies the text label as the name of the profile. For the ringing tone element, the processor 18 performs a transformation of the binary characters into ASCII characters and further the transformation of the ASCII characters into a ringing tone. For the graphic element, the processor

18 performs a transformation of the binary characters into a bit map file with the dimensions given in the element identifier, and if it is an animation the transformation is repeated for each image. All the individual elements are stored in a temporary memory.

5

Firstly the user may be asked whether to accept or reject, i.e. whether to store the profile in the permanent memory or not. If the user accepts the profile the processor 18 makes the profile available in the terminal for the user.

10 The profile concept has been discussed in detail in the applicant granted US patent serial no. 5.479.476. According to the preferred embodiment of the invention it will be possible to set the phone tones and profile graphic to work in a desired manner by selecting the desired setting group or "profile". This makes it easy to adjust the phone for different events and environments.

15

With reference to fig. 3 there is shown a short cut feature in the phone for selecting the desired profile. The idle state display (idle state is the home state of the phone in which it is waiting for any input from a user or a network), of the preferred embodiment of the phone according to the invention is shown as the first display in the sequence. The display 3 includes an operator logo 20 21 and a softkey label 22. By briefly pressing the "on/off"-key 4, the selectable profiles will be listed as selectable items 23 as an endless list in the display 3 together with a "switch off" the phone option. The desired profile is selected by moving a cursor 24 among the selectable items 23 – according to the preferred embodiment of the invention these items will include: "switch off", 25 "Personal", "Silent", "Discreet", "Loud" and possibly one or more further profiles created or stored by the user – and when the desired profile is highlighted the item, e.g. "Personal", is selected by pressing the softkey 8 having the softkey label 22 "OK", an information note shown in the third 30 display will inform the user about the selected profile "Personal tones in use".

After a few seconds the display will automatically change back to the idle state display shown as the first display in fig. 3. This will for some of the profiles include a small icon indicating that e.g. silent or discreet profile has been selected. The term highlighted is used for items in the display that are currently targeted for selection. There may be an inverted video bar (contrast invert) on the item to indicate the selection. When an item is highlighted, all user actions will be directed on the item.

However the full profile menu for editing, selection etc, has to be accessed by selecting "Menu" in idle state (first display of fig. 4) and thereby entering the menu structure of the phone by pressing the softkey 8. In the menu the user has to scroll through the list of selectable items 23 by using the cursor navigation key 10 – according to the preferred embodiment of the invention these items will include: "Phonebook", "Messages", "Call register", "Settings", "Call divert", "Games", "Calculator", "Clock", "Profiles" - for scrolling to the "Profiles" menu as illustrated in the second display in fig. 4, and select the highlighted item by pressing the softkey 8 having the softkey label 22 "Select".

When the user selects "Profiles" a list of selectable items will occur. This list will as indicated in the third display of fig. 4 include "Personal", "Silent", "Discreet", "Loud", "Profile name #1", "Profile name #2", where the last two items refer to one or more further possible profiles defined by the user or received from other users, while the first four items refers to profiles set from the factory. However some or all of these present profiles may also be edited. Now the user can move the cursor through the available profiles and select the desired one. No empty profiles will be listed.

According to the preferred embodiment of the invention the operation characteristics of the profile may be changed from the Profiles menu. Basically the following profiles are available:

- Personal – This is the default setting.
- Silent – Mutes all the phone tones. When the tones are off, a mute-icon is shown in standby mode.
- Discreet – Sets the phone tones to be quiet.
- 5 • Loud – Sets the phone tones to be loud.
- Empty#1 and Empty#2 profiles are defined in the phone or sent to the phone from a remote terminal for storing as profiles. Preferably these two profiles will not appear in the menu as selectable profiles as long as the profiles are empty. However when a profile has been defined the profile
- 10 name will occur as a selectable item in the profile list.

When the desired profile is highlighted the user selects the profile by pressing the softkey 8 now having the softkey label 23 "Option". When the user has selected one of the profiles e.g. "Personal" a list of selectable items will

15 appear. This list will as indicated in the fourth display of fig. 4 include "Use", "Personalise", and "Send". For editing a profile the cursor 24 has to highlight "Personalise" and the user has to press the softkey 8 having the softkey label 22 "OK". Then a list of selectable items will appear, and this list will as indicated in the fifth display of fig. 4 include adjustable settings as "Ringing

20 tone", "Ringing volume", "Incoming call alert", "Message alert tone", "Keypad tones", "Warning and game tones", " Vibrating alert ", and " Profile graphic ".

The menu item "Ringing tone" sets the ringing tone for voice calls. The user may scroll to the desired tone and select the highlighted ringing tone by

25 pressing the softkey 8 having the softkey label 22 "OK". The tones received from somebody or composed by the user himself can be found at the end of the tone list containing the tones pre-stored from the factory.

The menu item " Ringing volume " sets the volume level for the ringing tone. The user may scroll to the desired level and select the highlighted level by pressing the softkey 8 having the softkey label 22 "OK".

- 5 The menu item " Incoming call alert " defines how the phone notifies you of incoming voice calls. The options are: "Ringing", "Ascending", "Ring once", "Beep Once", and "Off". When Off is selected, all phone tones are mute and a mute icon is displayed. The user may scroll to the desired option and select the highlighted option by pressing the softkey 8 having the softkey label 22
- 10 "OK".

The menu item "Message alert tone" sets the volume level for tone message alert tone. The user may scroll to the desired level and select the highlighted level by pressing the softkey 8 having the softkey label 22 "OK".

15

The menu item "Keypad tones" sets the volume level for keypad tones. The user may scroll to the desired level and select the highlighted level by pressing the softkey 8 having the softkey label 22 "OK".

- 20 The menu item " Warning and game tones " sets the phone to sound a warning tone, for example when the battery is running out of power. This setting has no effect on the tones that are related to network services.

- 25 The menu item " Vibrating alert " sets the phone to vibrate when you receive a voice call or a text message. This setting can also set the phone to first vibrate and then ring. The vibrating alert is disabled when the phone is connected to a charger or a desktop stand.

- 30 The menu item "Profile graphic" sets the picture that is displayed in idle state after a selected period of time (called "timeout"). The user can select from a

couple of pre-stored animations or animations received from a remote terminal. An animation is a sequence of images being repeatedly refreshed in the display. The way this kind of animation works is explained in details in the patent US 5.870.683 in the name of the applicant.

5

In the profile graphic menu a first sub-menu item "Off,On" shows a previously selected profile graphic for a while, a second sub-menu item "Timeout" allows the user to set the time of the "timeout", while a third sub-menu item "Profile graphic" allows the user to select one of the available graphics. The operation
10 is terminated when the user selects the highlighted graphic or the entered input by pressing the softkey 8 having the softkey label 22 "OK" or interrupted by pressing the "clear"-key 9.

The menu item "rename" allows the user to rename the profile. The user then
15 selects a profile. The text editor of the phone is entered and the user may write the desired text, and this text becomes the new name of the selected profile by pressing the softkey 8 having the softkey label 22 "OK".

In the sixth display of fig. 4 the user may scroll through the entire list of
20 available ringing tones and select the one he prefers. The same is done for all the other selectable settings the user wants to set. When a ringing tone is selected in the sixth display by pressing the softkey 8 having the softkey label 22 "OK", the phone jumps to the higher menu level shown in the fifth display of fig. 4.

25

If the user does not want to change a setting he simply presses the "clear key" 9 and the phone goes one level up in menu. If the user continues to press the "clear key" 9 he will go one level up in menu each time until it reaches the idle state with the first display of fig. 4. Alternatively the idle state
30 may be reached by long pressing the "clear key" 9 (for more than 0.8 sec).

Profiles transferred to a mobile communication terminal (e.g. a cellular phone) via a wireless network connection may be called Over-The-Air profiles or OTA profiles. OTA profiles is a new way to personalise the phone according to personal preferences. Similarly to normal profiles (pre-stored in the phone), they are used to adjust the phone for different situations of use.

The phone can receive part of the profile settings including the profile name, ringing tone and profile graphic as a smart message. This combination of settings is called an OTA profile. According to the preferred embodiment of the invention the received profile settings can be stored to two replaceable profiles (preset OTA profiles). The profile, its ringing tone and its profile graphic all have the same name, for example, "Café". The profile name "Café" will replace the Empty#1 name mentioned above and will occur in the menu showing selectable profiles.

In this embodiment there is provided a method of handling operating characteristics of a profile in a mobile terminal, e.g. a cellular phone. The phone then has a number of user selectable profiles each including a group of user adjustable operating characteristics. Furthermore the phone is able to receive a message including a group of user adjustable operating characteristics from a remote terminal e.g. send as a message such as a SMS messages. Upon reception of such a message the phone analyses the message and identifies the individual user adjustable operating characteristics, and saves the group of user adjustable operating characteristics as a profile.

The graphics used in the profiles might be a simple bit-map image having a size fitting into the central part of the idle state display. Each pixel in such a bit-map image may in the most simple form only require one bit (black/white),

or additional bits may be used to include colour information. After a user adjustable timeout the bit-map image will stay in the display as long as the phone stays in idle state once it has been activated. A 40 times 25 bits image will therefor only require 125 bytes.

5

However more complex graphics may be desired and this may for example be provided as a sequence of simple bit-map images, e.g. 3-5 images, and these individual images are shown sequentially with a refresh time set by the user.

Advantageously these animations only have a duration corresponding to a few seconds. After the termination of the animation one of the images remains in the display for a while, e.g. 30 minutes, and the animation is repeated. However other events can trigger the animation, e.g. an input from a sensor detecting changes of the movements of the terminal.

15 FIG. 5 illustrates in a schematic way the structure of a mobile communications system and connections for transmitting short messages e.g. according to the GSM specification. Mobile stations or cellular phones 1 are connected to base stations 50 (BTS) by means of radio communication. The base stations 50 are further connected, through an Abis interface 51, to a base station controller
20 (BSC) 52, which controls and manages several base stations 50.

The entity formed by a number of base stations 50 and a single base station controller 52 is called a base station system (BSS) 53. The base station controller 52 manages radio communication channels and handovers.

25 Furthermore the base station controller 52 is connected to a mobile services switching centre (MSC) 54 via a so-called A-interface 55. The mobile services switching centre 54 co-ordinates the formation of connections both from and to mobile stations. The mobile service switching centre 54 connects the base station system 53 to the world outside the mobile communications network,

e.g. to a short message service centre (SM-SC) 55 managing the SMS activity in the mobile communications network.

When a user wants to send a short message (SMS) by means of the phone 1, he writes or retrieves from the memory a message to be transmitted and gives the phone number of receiver of the message, i.e., an identifier of a receiving phone 56, to where the message is going to be transmitted. When sending a short message, the message goes from the phone 1 to the base station 50, and from there, through the base station controller 52 and the mobile services switching centre 54, further to the short message service centre 55. The short message is stored at the short message service centre 55, from where it will be sent further to the receiving mobile station 56, and the route of the message will be in the same way as in transmission, but in the opposite direction. The short message service centre 55 will be informed whether or not the mobile station 56 has received the short message. If not the short message will be re-transmitted.

In addition to this, short messages can be sent from a Personal Computer (PC) 57 e.g. in a special Internet application available at some network operators home page available via the Internet 58. In this case, the mobile services switching centre 54 is in connection with a gateway server 59 (GTW), which again is in connection with the Internet 58. On this WWW page containing the special Internet message application, the user inputs the telephone number of the receiving phone 56 and the message to be transmitted, upon where the message can be sent from the Personal Computer (PC) 57, in which case it goes through the Internet 58 and the gateway server 59 to the mobile services switching centre 54 and further to the short message service centre 55, and further to the receiving phone 56 through the mobile communications network.

By means of the short message service (SMS) of the GSM system, it is presently possible to send a single message having a maximum length of which is 160 7-bit ASCII characters corresponding to 140 bytes. However by concatenating several individual messages into a concatenated message, a higher data content will be obtained.

Syntax of the profile transmission

The syntax of the profile transmission message is based on *<line-feed>* delimited presentation. The content is formatted as follows:

- 10 *<profile-message> ::= <profile-keyword><profile-body>*
<profile-keyword> ::= "Profile" <line-feed>; 'case-sensitive'
< profile-body > ::=
 [<name-field>] <line-feed> ; 'profile name'
 [<ringing-tone-field>] <line-feed> ;
 15 *<Ringing-Tone-programming-language>* (see below)
 [<ringing-volume>] <line-feed> ; 'ringing tone level'
 [<incoming-call-alert>] <line-feed> ; 'incoming-call-alert'
 [<message-alert-tone>] <line-feed> ; 'message-alert-tone'
 [<keypad-tones>] <line-feed> ; 'keypad-tones'
 20 *[<warning-tones>] <line-feed> ;* 'warning-tones'
 [<vibrating-alert>] <line-feed> ; 'vibrating-alert'
 [< graphic-field>] <line-feed> ;
 <OTA-bitmap> ::= <Header> <Image-data> (see below)
- 25 According to the preferred embodiment of the invention any of the supplementary information fields (*<ringing-tone-field>* to *< graphic-field>*) may be absent, but as the syntax requires, that the field separators (*<line-feed>*) must be present.
- 30 **Ringling tone format.**

The ringing tone format is handset independent, and describes only the audio related information. A tune is intended to be saved in the terminal. They can be used to implement message notification with a special ringing tone.

5 *<Ringing-Tone-programming-language> ::= <command>+*

<command> ::=

<command-length> <command-part>+ |

<command-end>

10 *<command-length> ::= 'binary [00000001 .. 11111111]. This indicates how many command parts there are in the command. If necessary, filler bits are added to ensure that <command-part> is always byte-aligned.'*

<command-end> ::= 'binary [00000000]; This indicates the end of the ringing tone programming language.'

15

<command-part> ::=

<ringing-tone-programming> |

<UNICODE> |

<cancel-command> <cancel-command-specifier> |

20

<sound> <sound-command-specifier>

The Ringing Tone programming requires that the order of the command parts is the following: *<ringing-tone-programming>*, [*<UNICODE>*], *<sound>*.

25 *<cancel-command-specifier> ::= <UNICODE>*

<sound-command-specifier> ::=

<basic-song-type> <basic-song> |

<basic-song> ::= <song-title> <temporary-song>

30 *<song-title> ::= <text-length> <text>*

<text> ::= <default-char>+ | ; 'UNICODE disabled'

<UNICODE-char>+ ; 'UNICODE enabled'

<text-length> ::= 'binary [0000 .. 1111] indicating how many characters are used for the following text. For example, in case of unicode, this counts the number of 16-bit unicode characters.'

<temporary-song> ::= <song-sequence-length> <song-sequence>

<song-sequence-length> ::= 'binary [00000000 .. 11111111]; Indicates how many song patterns follow.'

<song-sequence> ::= <song-pattern>+

10 <song-pattern> ::=

<pattern-header> |

<pattern-header> <pattern-instruction>+

<pattern-header> ::= <pattern-header-id> <pattern-id> <loop-value> <pattern-specifier>

15

<loop-value> ::= 'binary [0000 .. 1111]; Indicates how many times the pattern should be repeated. Value zero means no repeat. Value binary 1111 means infinite.'

20 <pattern-specifier> ::= <already-defined-pattern> | <length-of-the-new-pattern>

<already-defined-pattern> ::= 'binary [00000000]; This indicates that a already defined pattern is used again.'

25 <length-of-the-new-pattern> ::= 'binary [00000001 .. 11111111]; Indicates how many pattern instructions there are in the song pattern. Value zero is illegal.'

<pattern-instruction> ::=

<note-instruction> | <scale-instruction> | <style-instruction> |

<tempo-instruction> | <volume-instruction>

30

GRAPHICAL pictures and animations

The OTA bitmap format enables graphical information to be sent to a wide variety of handsets. Depending on the handset implementation, it may be possible for the user to create graphical objects and then send them to other handsets. The OTA bitmap format is handset independent, and describes only the graphical information.

The OTA bitmap syntax will according to the preferred embodiment according to the invention give the follow data:

```

< OTA- bitmap> ::= < Header> < Image- data>
< Header> ::= < InfoField> [< ExtField>]* < Width> < Height> < Depth>
< InfoField> ::= 'Octet which is defined in the Smart Messaging Specification'
15 < ExtField> ::= 'Octet which is defined in the Smart Messaging Specification'
< Width> ::= 'Horizontal width of the bitmap in pixels'
< Height> ::= 'Vertical height of the bitmap in pixels'
< Depth> ::= 'Number of colors or gray shades'
< Image- data> ::= < Main- image> [< Animated- image>]* ; 'There can be 0 to
20 15 animated images'
< Main- image> ::= 'Bitmap formed according to image data structure
description below'
< Animated- image> ::= 'Bitmap formed according to image data structure
description below'

```

25

If the bitmap is bigger than display the bitmap is cropped so that bitmap is shown starting from upper left corner to the lower right corner of the display. Scanning of the pixels in a plane will be done row by row. Rows will be scanned from top to bottom and pixels inside the row will be scanned from left

30 to right.

The embodiment described with reference to fig. 6 and 7 relates to an OTA profile message in which the message includes the profile name, a profile graphic acting as a screen saver, and a ringing tone. Fig. 6 shows a flow chart over the OTA Profile reception procedure and fig. 7 shows a sequence of displays upon reception of the OTA Profile. When an OTA profile is received (step 60), an SMS Alert tone is played. A soft notification 26 "OTA Profile received" is displayed (step 61). Soft notifications inform the user of events that have typically occurred without the user having been involved. Normally, they are shown as display text.

The incoming profile can be discarded by pressing the "Clear key" 9 (step 62). However, after the "Clear key" 9 has been pressed, a confirmation query (step 63) with text "Discard received profile?" will be displayed. The softkey label of the softkey 8 is "OK". By pressing the softkey 8 at step 64 the phone exits to idle state (step 65), and discards the received OTA profile without saving the profile. Pressing the "clear key" 9 instead of confirming the discarding will cancel the operation; in other words, the OTA profile is not deleted and the phone returns to the softkey option list at step 66.

20

When the user upon the soft notification (the second display of fig. 7) presses the softkey 8 having the softkey label 22 "Option" the phone 1 displays a selection list (in step 66) of the following selectable items:

25 Details
 Save
 Discard

The softkey function is "OK". By selecting "Details" from the option list shown as the third display of fig. 7, the phone will display a selection list 23 in step 70 of the selectable items:

30

- "Profile name" - when "Profile name" is highlighted 24, the softkey label 22 is "view" the name of the profile.
- "Ringing tone" - when "Ringing tone" is highlighted 24, the softkey label 22 is "playback" the ringing tone.
- 5 • "Profile graphic" – when "Profile graphic" is highlighted 24, the softkey label 22 is "view screensaver".
- "Save the profile".

When the user in step 71 selects the "Playback" softkey 8 the phone will play
 10 the received ringing tone for the user in step 72, and an information note 27
 will as shown items in the fifth display of fig. 7 be shown in the display 2. The
 softkey label 22 will change to "Quit" and the softkey functionality will be
 quitting the ringing tone playback. After the playing is interrupted or finished,
 the selection list with the selectable items (the fourth display of fig. 7) is
 15 displayed again.

When the user in step 71 selects "View screensaver" when "Profile graphic" is
 highlighted the phone will display the profile graphic to the user. The softkey
 label will be "Back" and the softkey functionality will be quitting the inspection
 20 of the graphics. After the inspection in step 72 is interrupted or finished, the
 selection list with the selectable items is displayed again.

If the user in step 67 selects "Save" from the softkey selection list (third
 display of fig. 7), or save from the details list in step 71, the phone displays an
 25 information note 27 as shown in the sixth display of fig. 7 with the display text
 "Select location for the profile". After this the phone displays as shown in the
 seventh display of fig. 7 all the profiles as a selection list. The user can in step
 68 select the profile to be replaced.

Normal mode.

30

Silent mode.

Discrete mode.

Outdoor mode.

OTA Profile 1 (pre-programmed)

OTA Profile 2 (pre-programmed)

5

After the selection, the Confirmation Query "Replace profile U" is displayed as an information note 27 if U is the name of the replaced profile as shown in the eighth display of fig. 7. The softkey label 22 is "OK". If the user confirms, the profile is saved in step 69 and a confirmation note 28 saying "OTA profile has

10 been saved" is displayed as shown in the ninth display of fig. 7, and the phone goes to the idle state.

Selecting "Discard" from the selection list in step 67, the phone will display the confirmation note query saying "Discard received profile" in step 63. If the

15 user confirms in step 64 by pressing the soft key, the downloaded OTA profile is discarded and the confirmation note query saying " Profile discarded" is displayed. After this, the phone goes to the idle state.

CLAIMS

1. A method of handling operating characteristics of a profile in a communication terminal, said communication terminal has a number of user selectable profiles each including a group of user adjustable operating characteristics, comprising
5 reception of a message including a group of user adjustable operating characteristics from a remote terminal transmitted via a communication channel,
and saving said group of user adjustable operating characteristics as a profile
10 in said communication terminal.
2. A method according to claim 1 wherein said message includes a ringing tone and at least one graphical picture for being stored in a profile selected by
15 the user.
3. A method according to claim 2 wherein the communication terminal allows the user to discard from a received profile message after inspection of items included in the profile message.
- 20 4. A method according to claim 2 wherein said at least one graphical picture includes a plurality of individual pictures, and said pictures are displayed successively in order to create an animation.
5. A method according to claim 1 wherein said message furthermore includes
25 a name label for the profile.
6. A communication terminal having a number of user selectable profiles each including a group of user adjustable operating characteristics, and comprising means for receiving messages, means for analysing the message type and
30 for detecting user adjustable operating characteristics when present in the

message, and means for storing user adjustable operating characteristics as one of said number of user selectable profiles available in said communication terminal.

- 5 7. A communication terminal according to claim 6 wherein said message includes a ringing tone and at least one graphical picture for being stored in a profile selected by the user.
- 10 8. A communication terminal according to claim 7 wherein the communication terminal has means for allowing the user to discard from a received profile message after inspection of items included in the profile message.
- 15 9. A communication terminal according to claim 7 wherein said at least one graphical picture includes a plurality of individual pictures, and the terminal has means for displaying said pictures successively in order to create an animation.
- 20 10. A communication terminal according to claim 6 wherein said message furthermore includes a name label for the profile.
- 25 11. A method of providing operating characteristics for a profile for a communication terminal, said communication terminal has a number of user selectable profiles each including a group of user adjustable operating characteristics, comprising arranging a group of user adjustable operating characteristics in a message having a predetermined message format, and transmitting said message to said communication terminal via a communication channel.

12. A method according to claim 11 wherein said message includes a ringing tone and at least one graphical picture for being stored in a profile selected by the user.

5 13. A method according to claim 12 wherein the communication terminal allows the user to discard a received profile message after inspection of items included in the profile message.

10 14. A method according to claim 12 wherein said at least one graphical picture includes a plurality of individual pictures, and said pictures are displayed successively in order to create an animation.

15 15. A method according to claim 11 wherein said message furthermore includes a name label for the profile.

16. A communication terminal having a number of user selectable profiles each including a group of user adjustable operating characteristics, and comprising means for arranging a group of user adjustable operating characteristics in a message having a predetermined message format, and
20 means for transmitting said message to said communication terminal via a communication channel.

25 17. A communication terminal according to claim 16 wherein said message includes a ringing tone and at least one graphical picture for being stored in a profile selected by the user.

18. A communication terminal according to claim 17 wherein the communication terminal has means for allowing the user to discard a received profile message after inspection of items included in the profile message.

19. A communication terminal according to claim 17 wherein said at least one graphical picture includes a plurality of individual pictures, and the terminal has means for displaying said pictures successively in order to create an animation.

5

20. A communication terminal according to claim 16 wherein said message furthermore includes a name label for the profile.

21. A communication terminal for receiving a profile message substantially as
10 herein before described with reference to the accompanying drawings.

22. A communication terminal for transmitting a profile message substantially as herein before described with reference to the accompanying drawings.

15 23. A method of handling OTA profile messaging substantially as herein before described with reference to the accompanying drawings.

ABSTRACT

A communication terminal has a number of user selectable profiles each including a group of user adjustable operating characteristics. These selectable profiles may be transferred from one communication terminal to another included in a message containing a group of user adjustable operating characteristics. When the communication terminal receives this message transmitted via a communication channel, it analyses the message and saves the group of user adjustable operating characteristics as a profile.

10

Fig. 2





Fig. 1

This Page Blank (uspto)

**Fig. 2**

This Page Blank (uspto)







Fig. 3

This Page Blank (uspto)


"Menu" has
been
selected.




"Profiles" has
been
selected.



"Silent" has
been
selected.



"Personalize"
has been
selected.



"Ringing
tone" has
been




Fig. 4

This Page Blank (uspto)





Fig. 5


This Page Blank (uspto)

Fig. 6




This Page Blank (uspto)

Ringing tone received.
Soft notification
displayed.




21 3 22

"Option" has
been
pressed.



26 22




24 23 22


"Details"
has been
selected.

"Playback" of the
ringing tone has
been selected.


"Save" has been
pressed in third
display.



24 23 22



27 22




27 22


"OK" has been
pressed or timeout
has expired.

"OTA profile 1"
has been
selected.


"OK" has been
pressed.



24 23 22



27 22



28

Fig. 7

This Page Blank (uspto)